

Socket connectors 1.27mm

Single row/double row/triple row
Solder tail, right angle












TEL:86-755-84106483 61121902
FAX:86-755-61121902
E-mail:ivan@pizconn.com.cn

Ordering information

TLB - NNN X - A P P 0920A

No. of Positions	Insulator Type code	Pin Plating code	Clip Plating code
	1 Single row	1 Tin150μ"	1 Tin150μ"
	2 Double row	2 Tin200μ"	2 Tin200μ"
	3 Triple row	3 GF	3 GF
		4 Gold2μ"	4 Gold2μ"
		5 Gold3μ"	5 Gold3μ"
		6 Gold10μ"	6 Gold10μ"
		7 Gold15μ"	7 Gold15μ"
		S Special	S Special

Series: TLB



Ultraminiature PCB socket connectors Solder tail right angle

Technical Specs:

Insulator:	Black glass filled polyester PPS-GF30-FR
Flammability:	UL 94V-O
Sleeve:	Brass CuZn 36pb3(36000)
Contact clip (3 finger):	Beryllium copper (C17200)
Mating pin Ø:	0.38 to 0.50 mm
Forces:	(polished steel gauge Ø 0.41mm)
-Insertion	0.5 N typ.
-Withdrawal	0.2 N typ.
Mechanical life:	min 500 cycles
Rated current:	1 A
Contact resistance:	max 10 mΩ
Dielectric strength:	min 500V RMS