| REVISION DATA | | | | |
|---|---|---|---|---|
| SYM | ECN | DESCRIPTION | DATE | APPROVED |
| | | | | |
| | | | | |













## Technical Data

Material:
Contact material: Brass
Insulator material:Black polyester UL94V-0
Standard:PBT+30%G.F

Electrical:
Current rating: 3Amps/contact max.
Contact resistance: ≤20mΩ/contact
Insulation resistance: ⩾1000MΩ at V=100V
Withstanding voltage:550V AC/minute

Mechanical:
Operating temperatures: Gold plated:-55° C to+105° C
Tin plated:-40° C to+105° C
Soldering temperature: +220° C,10s max.

| PHA2542 | XX | X | - | P | XX | X | X | A | XX |
|---|---|---|---|---|---|---|---|---|---|
| | High Option | Insulator Quantity | | | No. of Positions | Plating Option | Insulator Material Option | | Pin Length (A/B/C) |
| | 15 H=1.5mm<br>17 H=1.7mm<br>20 H=2.0mm<br>25 H=2.5mm | 1 1PCS<br>2 2PCS<br>3 3PCS<br>S Special | | | 04 to 80 | A G/F<br>B Au3μ"<br>C Au5μ"<br>D Au10μ"<br>E Au15μ"<br>S Special | A BK-PBT<br>B BK-PA66<br>C BK-PA6T<br>D BK-PA46<br>F BK-LCP<br>S Special | | 01~99 |

深圳平志电子有限公司
SHENZHEN PIZCONN ELECTRONIC CO.,LTD

Title: 2.54*2.54mm(0.1"*0.1")
Pin Header Dual Row Straight Dip Type

Part NO: PHA2542

UNIT: mm

E-mail: ivan@pizconn.com.cn