REVISION DATA				
SYM	ECN	DESCRIPTION	DATE	APPROVED



Single Row



Dual Row





Dual Row



Single Row

Technical Data

Material:
Contact material: Phosphor bronze
Insulator material:Black polyester UL94V-0
Standard:PBT+30%G.F

Electrical:
Current rating: 3Amps/contact max.
Contact resistance: ≤20mΩ/contact
Insulation resistance: ⩾1000MΩ at V=100V
Withstanding voltage:550V AC/minute

Mechanical:
Operating temperatures: Gold plated:-55° C to+105° C
Tin plated:-40° C to+105° C
Soldering temperature: +220° C,10s max.

FDA2541	X	XX	0 - U	XX	X	X	A	XX
	Row Option 1 Single Row 2 Dual Row	High Option 50 H=5.0mm 85 H=8.5mm		No. of Positions 02 to 40 04 to 80	Plating Option A G/F B Au3μ" C Au5μ" D Au10μ" E Au15μ" S Special	Insulator Material Option A BK-PBT B BK-PA66 C BK-PA6T D BK-PA46 F BK-LCP S Special		Pin Length 01~99

深圳平志电子有限公司
SHENZHEN PIZCONN ELECTRONIC CO.,LTD

Title: 2.54mm(0.1")
Female Header Straight Dip Type

Part NO: FDA2541

UNIT: mm

E-mail: ivan@pizconn.com.cn